

Hypersperse* MSI310

FACT SHEET

Antiscalant/Antifoulant

- Certified for use in producing potable water (Certified to NSF/ANSI Standard 60)
- Effectively controls scales including silica, calcium carbonate, calcium sulfate, barium sulfate, and strontium sulfate
- May be fed neat or diluted
- Compatible with all the leading RO membranes
- Includes uniquely effective Veolia polymer
- Maintains cleaner membrane surfaces by dispersing particulate foulants
- Effective over a wide pH range. Compatible with feedwaters that contain aluminum and iron oxides

Description and Use

Hypersperse MSI310 is a highly effective liquid antiscalant/antifoulant specifically designed for silica scale. Hypersperse MSI310 includes a proprietary Veolia polymer which is uniquely effective in preventing silica scale. This is an enhancement to Hypersperse MSI300, which is the only silica inhibitor with extensive field and pilot study data demonstrating efficacy on membrane systems applications. Data show effective control of silica up to 240 ppm, although applications on various water sources may establish even higher limits. Use of this product provides longer run times and extended element life resulting in reduced operating and capital costs.

Packaging Information

Hypersperse MSI310 is a liquid material available in a wide variety of customized containers and delivery methods. Contact your Veolia sales representative for details.

Application

For maximum effectiveness, Hypersperse MSI310 should be added prior to the static mixer or cartridge filter housing. It can be fed neat (undiluted) directly from the shipping container or can be diluted (see below).

For potable applications, the maximum dosage is 10 mg/L. Maximum recommended dilution is 10% with RO permeate or DI water at typical operating temperatures (<30°C (<86°F)).

Dosing

Typical dosage range is between 3 and 6 mg/L.

Contact your local Veolia representative to define the optimal feed point and dosage rate.

Maximum Dilutions

Maximum dilution is temperature related as shown below.

Temperature, °C	Maximum Dilution, %
<30	10
30-35	25
>35	50

Safety Precautions

A Safety Data Sheet containing detailed information about this product is available on request.